

**Aerospace Part#:** 1288spcdu

**CONTROL CABLE**

**DESCRIPTION**

2 Conductors AWG 22/19x34 TC  
Overall SPC Braid Shield FEP/FEP White

**PHYSICAL PROPERTIES**

**Conductors**

**Insulation**

# Conductors	AWG	Material	Material	Wall	Finished OD
2	22/19x34	Silver Plated Copper	FEP	.010"	.050"

**Outer Braid Material**

**Drain Wire**

Layer Type	Material	AWG	Coverage	AWG	Material
Each Conductor Braid Shield	Silver Plated Copper	38	95%	20/19x32	Silver Plated Copper

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	White	.010"	.138" x .118" Nom.	Parallel

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	23 lbs / m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage	Capacitance (Cond. To Drain)
300 Volt	55 pf / ft nom.

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

**MISCELLANEOUS**

Color Code: Black / Clear /

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice