



Aerospace Part#: 1298/19w

CONTROL CABLE

DESCRIPTION

2 Conductors AWG 24/19x36 TC

Overall Braid Shield FEP/FEP White 600V 200C

PHYSICAL PROPERTIES

Conductors			Insulation			
# Conductors AWG		Material Material		Wall	Finished OD	
2	24/19x36	Tinned Copper	FEP	.010"	.043"	

Outer Braid Material

Layer 1 Type	Material	AWG Coverage	
Overall Braid Shield	Tinned Copper	36	90%

Outer Jacket Material				Cabling		
	Jacket Material	Color	Wall	Overall O.D.	Lay	
	FEP	White	.015"	.139" Nom.	2" Lay on Cable with Clear Mylar	

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	17.0 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage	
Rated 600 Volts	

INDUSTRY APPROVALS AND COMPLIANCE

Standar	ds & Environmental Programs				
	Reach / RoHS Compliant		YES		
MISCEL Color Code:	LANEOUS Black / White /				
	Contact Us For More Information T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com				
	LOW MINIMUM RU	INS QUICK TUR	NAROUNDS CUSTOM C	ABLE SOLUTION	6 MADE IN USA

 * Specification subject to error $% \left(\mathcal{A}^{\prime}\right) =\left(\mathcal{A}^{$