

**Aerospace Part#:** 1325kks

**CONTROL CABLE**

**DESCRIPTION**

3 Conductors AWG 14/19x.015" TC  
Unshield E-CTFE/E-CTFE Natural 600V 150C

**PHYSICAL PROPERTIES**

**Conductors**

**Insulation**

# Conductors	AWG	Material	Material	Wall	Finished OD
3	14/19x.015"	Tinned Copper	E-CTFE	.015"	.100"

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
E-CTFE	Natural	.012"	.239" Nom.	4" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -40C to 150C	49.5 lbs / m	15 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
Rated 600 Volts

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Flame Test	NFPA 262 / FT6

**MISCELLANEOUS**

Color: Black / White / Green /  
Code:

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice