



## Underwriter Laboratory Approvals (cont.)

| FEP UL STYLE NUMBERS |             |               |                        |                 |                         |  |
|----------------------|-------------|---------------|------------------------|-----------------|-------------------------|--|
| UL STYLE #           | UL TEMP. °C | UL VOLTAGE AC | AVERAGE WALL THICKNESS | INSULATION TYPE | CONDUCTOR SIZES AWG.    | BASIC CONDUCTOR TYPES (Check for Specials) |
| 1226                 | 80          | N/S           | .008                   | FEP             | 32-20                   | BARE, TPC, SPC, NPC                        |
| 1226                 | 80          | N/S           | .013                   | FEP             | 19-14                   | BARE, TPC, SPC, NPC                        |
| 1227                 | 105         | N/S           | .008                   | FEP             | 32-20                   | BARE, TPC, SPC, NPC                        |
| 1227                 | 105         | N/S           | .013                   | FEP             | 19-14                   | BARE, TPC, SPC, NPC                        |
| 1330                 | 200         | 600           | .020                   | FEP             | 30-10                   | SPC, NPC                                   |
| 1330                 | 200         | 600           | .030                   | FEP             | 8-2                     | SPC, NPC                                   |
| 1330                 | 200         | 600           | Per AWG.               | FEP             | Larger than .015 strand | TPC  |
| 1331                 | 150         | 600           | .020                   | FEP             | 30-10                   | TPC, SPC, NPC                              |
| 1331                 | 150         | 600           | .030                   | FEP             | 8-2                     | TPC, SPC, NPC                              |
| 1332                 | 200         | 300           | .013                   | FEP             | 30-10                   | SPC, NPC                                   |
| 1332                 | 200         | 300           | .013                   | FEP             | Larger than .015 strand | TPC  |
| 1333                 | 150         | 300           | .013                   | FEP             | 30-10                   | TPC, SPC, NPC                              |
| 1371                 | 105         | N/S           | .0055                  | FEP             | 32-20                   | TPC, SPC, NPC                              |
| 1371                 | 105         | N/S           | .008                   | FEP             | 19-16                   | TPC, SPC, NPC                              |
| 1371                 | 105         | N/S           | .013                   | FEP             | 15-10                   | TPC, SPC, NPC                              |
| 1371                 | 105         | N/S           | .020                   | FEP             | 9-6                     | TPC, SPC, NPC                              |
| 1538                 | 105         | 125           | .0055                  | FEP             | 36-20                   | TPC, SPC, NPC                              |
| 1538                 | 105         | 125           | .008                   | FEP             | 19-15                   | TPC, SPC, NPC                              |
| 1538                 | 105         | 125           | .013                   | FEP             | 14-10                   | TPC, SPC, NPC                              |
| 1538                 | 105         | 125           | .020                   | FEP             | 9-6                     | TPC, SPC, NPC                              |
| 1577                 | 200         | N/S           | .012                   | FEP             | 32-16                   | TPC, SPC, NPC, A                           |
| 1591                 | 150         | 300           | .016                   | FEP             | 26-16                   | TPC, SPC, NPC                              |
| 1716                 | 150         | 150           | .010                   | FEP             | 32-10                   | TPC, SPC, NPC                              |
| 1716                 | 150         | 150           | .020                   | FEP             | 9-6                     | TPC, SPC, NPC                              |
| 1723                 | 200         | N/S           | .010                   | FEP             | 32-16                   | SPC, NPC                                   |
| 1886                 | 150         | 300           | .010                   | FEP             | 30-10                   | TPC, SPC, NPC                              |
| 1887                 | 150         | 600           | .014                   | FEP             | 30-10                   | TPC, SPC, NPC                              |
| 1887                 | 150         | 600           | .020                   | FEP             | 8-2                     | TPC, SPC, NPC                              |
| 1900                 | 200         | 300           | .010                   | FEP             | 30-10                   | SPC, NPC                                   |
| 1900                 | 200         | 300           | .010                   | FEP             | Larger than .015 strand | TPC  |
| 1901                 | 200         | 600           | .014                   | FEP             | 30-10                   | SPC, NPC                                   |
| 1901                 | 200         | 600           | .020                   | FEP             | 8-2                     | SPC, NPC                                   |
| 1901                 | 200         | 600           | Per AWG.               | FEP             | Larger than .015 strand | TPC  |

N/S = Voltage not specified by UL      FEP = Fluorinated Ethylene Propylene      UL File # E 67145

| PFA UL STYLE NUMBERS |             |               |                        |                 |                      |  |
|----------------------|-------------|---------------|------------------------|-----------------|----------------------|--|
| UL STYLE #           | UL TEMP. °C | UL VOLTAGE AC | AVERAGE WALL THICKNESS | INSULATION TYPE | CONDUCTOR SIZES AWG. | BASIC CONDUCTOR TYPES (Check for Specials) |
| 1726                 | 250         | 300           | .013                   | PFA             | 32-10                | NPC  |
| 1726                 | 250         | 300           | .020                   | PFA             | 8-6                  | NPC  |
| 1726                 | 250         | 300           | .030                   | PFA             | 4-2                  | NPC  |
| 1727                 | 250         | 600           | .020                   | PFA             | 32-10                | NPC  |
| 1727                 | 250         | 600           | .030                   | PFA             | 8-2                  | NPC  |
| 10362                | 250         | 600           | .010                   | PFA             | 30-10                | NPC  |
| 10590                | 200         | 1000          | .020                   | PFA             | 32-10                | SPC  |
| 10590                | 200         | 1000          | .030                   | PFA             | 8-2                  | SPC  |
| 10590                | 250         | 1000          | .020                   | PFA             | 32-10                | NPC  |
| 10590                | 250         | 1000          | .030                   | PFA             | 8-2                  | NPC  |