

Aerospace Part#: 1336b

CONTROL CABLE

DESCRIPTION

3 Conductors AWG 16/19x29 TC
Overall Foil Shield FEP/FEP Black 600V 200C

PHYSICAL PROPERTIES

Conductors

Insulation

| # Conductors | AWG | Material | Material | Wall | Finished OD |
|--------------|----------|---------------|----------|-------|-------------|
| 3 | 16/19x29 | Tinned Copper | FEP | .012" | .077" |

Outer Shield Material

Drain Wire

| Layer 1 Type | Material | Coverage | AWG | Material |
|---------------------|--------------|----------|----------|---------------|
| Overall Foil Shield | Alum / Mylar | 100% | 16/19x29 | Tinned Copper |

Outer Jacket Material

Cabling

| Jacket Material | Color | Wall | Overall O.D. | Lay |
|-----------------|-------------|-------|--------------|----------------------------------|
| FEP | Solid Black | .015" | .200" Nom. | 3" Lay on Cable with Clear Mylar |

MECHANICAL PROPERTIES

| Operating Temp | Total Weight | Bend Radius |
|--------------------|--------------|-------------|
| Rated -80C to 200C | 46.3 lbs / m | 10 X OD |

ELECTRICAL PROPERTIES

| Max. Operating Voltage |
|------------------------|
| Rated 600 Volts |

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

| | |
|------------------------|-----|
| Reach / RoHS Compliant | YES |
|------------------------|-----|

MISCELLANEOUS

Color: Black / Red / White /
Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice