Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



83046 Hook-up/Lead - UL AWM Style 1371

For more Information please call

1-800-Belden1




General Description:

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

Physical Characteristics (Overall)

AWG:



Total Number of Conductors:

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
TFE - Tetrafluoroethylene	0.1524

Overall Insulation

Overall Cable

Overall Nominal Diameter: 0.787 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs	

photosic change of Entricement of Control			
UL Rating:	105°C		
EU Directive 2011/65/EU (ROHS II):	Yes		
EU CE Mark:	Yes		
EU Directive 2000/53/EC (ELV):	Yes		
EU Directive 2002/95/EC (RoHS):	Yes		
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005		
EU Directive 2002/96/EC (WEEE):	Yes		
EU Directive 2003/11/EC (BFR):	Yes		
CA Prop 65 (CJ for Wire & Cable):	Yes		
MII Order #39 (China RoHS):	Yes		
Military Specification:	NEMA HP3, MIL-W-16878/6		
MIL Spec Rating:	250 V, 200°C		
ame Test			

UL Flame Test:

Plenum/Non-Plenum

Plenum (Y/N): No

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83046 0011000	1,000 FT	2.000 LB	BROWN	ES	#26 STR TFE BRN
83046 0021000	1,000 FT	2.000 LB	RED	ES	#26 STR TFE RED
83046 0031000	1,000 FT	2.000 LB	ORANGE	ES	#26 STR TFE ORG
83046 0041000	1,000 FT	2.000 LB	YELLOW	ES	#26 STR TFE YEL
83046 0061000	1,000 FT	2.000 LB	BLUE, LIGHT	ES	#26 STR TFE BLULT
83046 007100	100 FT	0.200 LB	VIOLET	E	#26 TFE VIO
83046 0071000	1,000 FT	2.000 LB	VIOLET	ES	#26 TFE VIO
83046 009100	100 FT	0.200 LB	WHITE	E	#26 STR TFE WHT
83046 0091000	1,000 FT	2.000 LB	WHITE	ES	#26 STR TFE WHT
83046 0101000	1,000 FT	2.000 LB	BLACK	ES	#26 STR TFE BLK

Notes:

Page 1 of 2 11-05-2015

Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



83046 Hook-up/Lead - UL AWM Style 1371

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25' S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER10

Revision Number: 1 Revision Date: 07-10-2012

© 2015 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 2 of 2 11-05-2015