



For more Information  
please call

1-800-Belden1



### General Description:

14 AWG stranded (19x26) bare copper conductors, PVC/Nylon insulation, PVC jacket.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
1	14	19x26	BC - Bare Copper

Total Number of Conductors: 1

#### Ground Wire

Ground Wire (Y/N): N

#### Insulation

Insulation Material:

Insulation Material	Wall Thickness (in.)
PVC/Nylon - Polyvinyl Chloride/Nylon	.021

#### Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (in.)
PVC - Polyvinyl Chloride	.030

#### Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	Black

Overall Nominal Diameter: 0.250 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +90°C

Bulk Cable Weight: 27 lbs/1000 ft.

Max. Recommended Pulling Tension: 55 lbs.

Min. Bend Radius/Minor Axis: 2.500 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

IMSA Specification: 51-5

#### Suitability

Suitability - Outdoor: Yes

## 580206 Multi-Conductor - Spec 51-5 Loop Detector Wire

Suitability - Burial: Yes

**Plenum/Non-Plenum**

Plenum (Y/N): No

**Electrical Characteristics (Overall)**

**Nom. Conductor DC Resistance:**

**DCR @ 20°C (Ohm/1000 ft)**

2.520

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
580206 0032500	2,500 FT	80.000 LB	ORANGE		#14 STR PVC/NYL PVC
580206 0035000	5,000 FT	165.000 LB	ORANGE		#14 STR PVC/NYL PVC
580206 0102500	2,500 FT	80.000 LB	BLACK		#14 STR PVC/NYL PVC
580206 0105000	5,000 FT	165.000 LB	BLACK		#14 STR PVC/NYL PVC

Revision Number: 1    Revision Date: 08-20-2012

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.