	TECHNICAL DATA SHEET	code	4100UE
		version	4
		date	2012-09-19
	4100UE NON-PAIRED	page	1/2

APPLICATION

Commercial applications

CONSTRUCTION



1. Conductor

Diameter of conductor 1.8 mm (AWG14)
Material stranded bare copper (19xAWG27)

2. Insulation

Material Polyolefin
Diameter over insulation 2.34 ± 0.05 mm
Wall thickness 0.28 mm

3. Overall Cabling

Colour code black – white

4. Sheath

Material FRNC
Colour Grey
Nominal thickness 0.4 mm
Nominal diameter 5.55 mm


REQUIREMENTS AND TEST METHODS

Electrical:

Nominal resistance conductor 8.3 Ω /km
Nom. capacitance conductor to conductor @ 1kHz 270 pF/m
Testvoltage conductor-conductor 2500 VDC, 3 seconds
Voltage rating 300 V RMS
Maximum continues current per conductor @ 25 °C 8 A per conductor @ 25 °C

Mechanical and physical:

Temperature range processing and operating -20 to +70 °C
Temperature range storage -30 to +70 °C
Minimum bending/setting radius $5 \cdot D / 10 \cdot D$
Maximum pulling tension 56 N
Halogen free according to IEC 60754-1
Non dense smoke according to IEC 61034-1 and 61034-2
Non corrosive gas according to IEC 60754-2
Flame Retardant according to IEC 60332-1

	TECHNICAL DATA SHEET	code	4100UE
		version	4
		date	2012-09-19
	4100UE NON-PAIRED	page	2/2



Belden declares this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.

© Belden Wire & Cable B.V.

All rights are reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner