

**Aerospace Part#:** 1326SPC

**CONTROL CABLE**

**DESCRIPTION**

3 Conductors AWG 14/19x27 SPC  
Overall Foil Shield 600V FEP/FEP Gray

**PHYSICAL PROPERTIES**

**Conductors**

**Insulation**

# Conductors	AWG	Material	Material	Wall	Finished OD
3	14/19x27	Silver Plated Copper	FEP	.012"	.091"

**Outer Shield Material**

**Drain Wire**

Layer 1 Type	Material	Coverage	AWG	Material
Overall Foil Shield	Alum / Mylar	100%	16/19x29	Tinned Copper

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Gray	.015"	.230" Nom.	4" Lay on Cable with Clear Mylar

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	60.1 lbs / m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage	Capacitance (Cond. To Cond.)
Rated 600 Volts	34.3 pf / ft nom.

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Flame Test	NFPA 262 / FT6

**MISCELLANEOUS**

Color: Black / Red / White /  
Code:

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice