



Hueson Wire
 134 Ferry St.
 South Grafton, Ma 01560
 www.huesonwire.com

Issue Date: 6/26/2020

Construction

Issue: 1

Description: 2/PR 14 41/30 TC SR-PVC/PVC		Diam. (In)
Component:	Conductors	
Conductor:	14 AWG 41/30 Tinned Copper to ASTM B-174	0.070 "
Insulation:	0.01" SR PVC 0.09 +/- .003"	0.090 "
Color Code:	Black+Brown, Red+Orange	0.090 "
Cable Assembly	Twist the 4 Conductors Into Twisted Pairs	0.153 "
Cable Assembly:	Bunch Cable the 2 Twisted Pairs	0.297 "
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	"
Binder:	Non-Woven Polyester or Clear Mylar Tape Binder	0.301 "
Jacket:	0.035" Flexible PVC, Oil, Moisture UV Resistant, VW-1	0.370 "
Jacket Color:	Gray 0.37 +/- 0.010"	0.370 "

Print: E174416 AWM-2464 80C 300V VW1 cRU AWM A/B I/II 80C 300V FT-1

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>		
UL	AWM-2464	80°C	300	VW-1		
Canadian cRU	AWM	80°C	300	FT-1	I/II	A/B

- Environmental Compliance**
- RoHS EU Directive 2011/65/EU (1&2&3)
 - REACH Regulation 205:
 - California Prop 65:

Issue Date: 6/26/2020

Issue: 1

Drawing/Rotation:

