



PLENUM CABLE Aerospace Part#: 2210

DESCRIPTION

2 Pairs AWG 14/19x.015" TC Overall Foil Shield FEP/FEP Gray CL2P

PHYSICAL PROPERTIES

| Pairs | | | | Insulation | | | |
|-------|---------|-------------|---------------|------------|-------|-------------|--|
| | # Pairs | AWG | Material | Material | Wall | Finished OD | |
| | 2 | 14/19x.015" | Tinned Copper | FEP | .007" | .084" | |

| Outer Shield Material | | Drain Wire | | | |
|-----------------------|--------------|------------|----------|---------------|--|
| Shield Type | Material | Coverage | AWG | Material | |
| Overall Foil Shield | Alum / Mylar | 100% | 16/19x29 | Tinned Copper | |

Outer Jacket Material Cabling

| Jacket Material | Color | Wall | Overall O.D. | Lay |
|-----------------|-------|-------|--------------|---|
| FEP | Gray | .012" | .322" Nom. | 2" Lay on Pair 4" Lay on Cable with Clear Mylar |

MECHANICAL PROPERTIES

| Operating Temp | Total Weight | Bend Radius |
|-----------------------|--------------|-------------|
| UL Rated -80C to 200C | 76.2 lbs/m | 10 X OD |

ELECTRICAL PROPERTIES

| | Max. O | perating \ | Voltage | |
|---|---------|------------|----------------|--|
| ı | JL Rate | d 150V Po | wer Ltd. | |

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

| otandardo di Environmontari rogramo | | | | | |
|-------------------------------------|---|--|--|--|--|
| RoHS Compliant | YES | | | | |
| Suitability | Indoor, Direct Burial, Wet Location | | | | |
| Resistance | Oil, Gas, Sunlight, Abrasian, Acid | | | | |
| Applications | Audio, Control, Instrumentation Remote, Signaling, Power-limited systems | | | | |
| Flame Test | NFPA 262 | | | | |
| NEC / (UL) Specification | CL2P | | | | |

MISCELLANEOUS

Markings: E111036 TYPE CL2P 200C FEP/FEP 14 AWG (UL)

Color

Black/Red Black/White Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

^{*} Specification subject to error and may change without notice