



ATLAS WIRE LLC.  
 9525 RIVER STREET  
 SCHILLER PARK, ILLINOIS 60176  
 (847) 678-1210  
 (847) 678-1281 FAX  
 www.atlaswirecorp.com



Atlas Wire, LLC  
 Registered to ISO9001 and TS16949  
 Schiller Park, IL 60176  
 Reference No. 10000854  
 Tucson, AZ 85714  
 Reference No. 10003647

## MATERIAL SPECIFICATION SHEET

#14 19/0147 TOPCOAT 1/32" PVC  
 RoHS COMPLIANT

AWM STYLES 1015, 1230 105c-600v OR  
 AWM STYLES 1013, 1335 90c-600v OR AWM STYLE 1032 90c-1000v VW1  
 CSA TEW 105c-600v OR AWM I A/B 105c-600v OR  
 CSA TR-32 90c – Oil and Water Resistant 75c FT1

<b>CONDUCTOR:</b>	#14 10/0147 TOPCOAT 1" LAY	
	NOMINAL O.D.	.072"
	APPROXIMATE CIRCULAR MILL AREA	4,106
	WEIGHT PER THOUSAND FEET	12.8#
	BASIC SPECIFICATION	ASTM B 470 TYPE 1
<b>PVC:</b>	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	330% AVERAGE
	TENSILE STRENGTH	2450 PSI AVERAGE
	SPECIFIC GRAVITY	1.32
	DUROMETER (SHORE)	91 (A)
	OXYGEN INDEX	28
	BRITTLE POINT	-24c
	SPARK TESTED	10,000 VOLTS
	WALL THICKNESS	.031"
	NOMINAL OVERALL DIAMETER	.134"
	WEIGHT PER THOUSAND FEET	18.83#
<b>USE:</b>	INTERNAL WIRING OF APPLIANCES; OR INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c. UL 1230, 1335 – MOISTURE RATING 60C UL 1032 – 3,500V PEAK FOR ELECTRONIC USE ONLY UL 1015, 1013 – 2,500V PEAK FOR ELECTRONIC USE ONLY.	

info@atlaswirecorp.com