



## PRODUCT INFORMATION SHEET

# Copper Battery Cable

4/0 2109X30T 3614 BK

125°C

---

### Conductor

Size: 4/0  
Number of Strands: 2109  
Strand Diameter, Nom: 30 GA  
Conductor: Tinned Copper

---

### Insulation

Insulation Material: 125°C EPDM  
Min Wall: 1.62 mm ( 0.064 in )  
Min Average Wall: 2.03 mm ( 0.080 in )  
Diameter, Nom: 19.80 mm ( 0.780 in )  
Strip Force, Min: 4 lbs. ( 17.8 N )  
Strip Force, Max: 40 lbs. ( 178.0 N )  
Separator: Physical

---

Voltage Rating: 600V  
Temperature Rating: -40°C to 125°C  
Specifications: UL: 3340/3374/3614  
CSA: CL-1503/AWM  
DPA: ES-215 (Print)  
DPA: ES-235 (Strip Force)  
Part Number: 145946-81IE  
Packaging: Reels  
Print Legend: 4/0 AWG (UL LOGO) AWM STYLE 3340 OR 3374 OR 3614 125C/150C  
600V/1000V PRESTOLITE PG CSA CL 1503 OR AWM I A/B 125C 600V FT2  
Color: Black  
Other: RoHS compliant