

Aerospace Part#: 1465JI

DESCRIPTION

4 Conductors AWG 20/7x28 TC
Unshielded FEP/FEP Gray CL3P & UL AWM 1887 Inners Style 20712

PHYSICAL PROPERTIES

Conductors		Insulation			
# Conductors	AWG	Material	Material	Wall	Finished OD
4	20/7x28	Tinned Copper	FEP	.016"	.070"

Outer Jacket Material		Cabling			
Jacket Material	Color	Wall	Overall O.D.	Lay	
FEP	Gray	.015"	.199" Nom.	4" Lay on Cable	

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
UL Rated -80C to 150C	33.1 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
UL Rated 600 Volts

INDUSTRY APPROVALS AND COMPLIANCE

UL AWM	1887, 20712
Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid
Applications	Audio, Control, Instrumentation Remote, Signaling, Power-limited systems
Flame Test	NFPA 262
NEC / (UL) Specification	CL3P

MISCELLANEOUS

Markings: E111036 TYPE CL3P (UL) - E157093 AWG 20 AWM STYLE 1887, 20712 150C 600V c RU us

Color Code: Black / Red / White / Green /

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice