

Multi-Conductor, Unshielded

UL 2464, UL 2587, NEC Type CL3 and CM (UL) c(UL), CSA CMG



Product Construction:

Conductor:

- 16 thru 12 AWG fully annealed stranded tinned copper per ASTM B-33

Insulation:

- Premium-grade, color-coded PVC
- Color code: See chart below

Jacket:

- PVC, gray
- Temperature range: -20°C to +90°C

Applications:

- Public address systems
- Intercoms
- Internal telephones
- Remote control circuits
- Suitable for EIA RS-232 applications
- Suggested voltage rating: 300 volts

Compliances:

- NEC Article 725 Type CL3 (UL: 75°C)
- NEC Article 800 Type CM (UL: 75°C)
- UL Style 2464 (UL: 80°C, 300V)
- UL Style 2587 (UL: 90°C, 600V)
- CSA CMG (CSA: 60°C)
- RoHS Compliant Directive 2002/95/EC
- Designed to meet UL 70,000 BTU Vertical Tray Flame Test
- Passes CSA CMG Flame Test

Packaging:

- Please contact Customer Service for packaging and color options

| CATALOG NUMBER | NO. OF COND. | AWG SIZE | COND. STRAND | NOM. INSULATION THICKNESS | | NOM. JACKET THICKNESS | | NOMINAL O.D. | | NOM. C-C CAP* pF/ft |
|----------------|--------------|----------|--------------|---------------------------|----|-----------------------|----|--------------|----|---------------------|
| | | | | INCHES | mm | INCHES | mm | INCHES | mm | |

NEC TYPE CM, UL STYLE 2464 (80°C, 300 VOLTS)

| | | | | | | | | | | |
|--------|----|----|----------|-------|------|-------|------|-------|-------|------|
| C2405A | 2 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.260 | 6.81 | 30.5 |
| C2406A | 3 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.283 | 7.19 | 30.5 |
| C2425A | 4 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.306 | 7.77 | 30.5 |
| C2434A | 5 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.334 | 8.48 | 30.5 |
| C2426A | 7 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.363 | 9.25 | 30.5 |
| C2443A | 8 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.393 | 10.03 | 30.5 |
| C2435A | 9 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.423 | 10.80 | 30.5 |
| C2427A | 12 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.476 | 12.17 | 30.5 |
| C2428A | 15 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.530 | 13.46 | 30.5 |
| C2429A | 19 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.559 | 14.33 | 30.5 |
| C2436A | 25 | 16 | 19/.0117 | 0.021 | 0.53 | 0.032 | 0.81 | 0.657 | 16.69 | 30.5 |

NEC TYPE CL3, UL STYLE 2587 (90°C, 600 VOLTS)

| | | | | | | | | | | |
|---------|---|----|-----------|-------|------|-------|------|-------|-------|------|
| C2409A† | 2 | 14 | 19/.0147 | 0.030 | 0.81 | 0.032 | 0.81 | 0.326 | 8.51 | 29.0 |
| C2430A | 4 | 14 | 19/.0147 | 0.032 | 0.81 | 0.032 | 0.81 | 0.391 | 9.93 | 28.2 |
| C2437A | 5 | 14 | 19/.0147 | 0.032 | 0.81 | 0.032 | 0.81 | 0.428 | 10.87 | 28.2 |
| C2431A | 7 | 14 | 19/.0147 | 0.032 | 0.81 | 0.032 | 0.81 | 0.469 | 11.91 | 28.2 |
| C2410A | 2 | 12 | 19/0.0185 | 0.032 | 0.81 | 0.032 | 0.81 | 0.366 | 9.40 | 31.0 |
| C2440A | 4 | 12 | 19/0.0185 | 0.032 | 0.81 | 0.032 | 0.81 | 0.437 | 11.02 | 31.0 |

*Capacitance between conductors
†CL3, UL2587, CSA CMH Only

Color Code Chart Per ICEA

| NO. OF COND. | COLOR | NO. OF COND. | COLOR | NO. OF COND. | COLOR |
|--------------|-------------|--------------|--------------|--------------|-------------------|
| 1 | Black | 10 | Orange/Black | 19 | Blue/Red |
| 2 | White | 11 | Blue/Black | 20 | Red/Green |
| 3 | Red | 12 | Black/White | 21 | Orange/Green |
| 4 | Green | 13 | Red/White | 22 | Black/White/Red |
| 5 | Orange | 14 | Green/White | 23 | White/Black/Red |
| 6 | Blue | 15 | Blue/White | 24 | Red/Black/White |
| 7 | White/Black | 16 | Black/Red | 25 | Green/Black/White |
| 8 | Red/Black | 17 | White/Red | | |
| 9 | Green/Black | 18 | Orange/Red | | |



Designed to Meet
UL Vertical Tray
Flame Test

Underwriters Laboratories Inc.

