

150-52693

Article Number: 150-52693

Description: Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg



Base Data	
Local Order Number	150-52693
Type	T50SOSFT6SD
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
Quantity Per	bag
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
GLOBAL PART NAME	T50SOSFT6SD-PA66HS/PA66HIRHS-BK
Short Description	Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225N
Length L (Imperial)	6.0"
Length L (Metric)	150mm
Length L2 (Imperial)	0.5"
Fixation Method	Fir Tree
Identification Plate Position	none
Length L2 (Metric)	11.6mm
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.18"
Width W (Metric)	4.6mm

150-52693



Product Dimensions	Width W2 (Imperial)	0.35"
	Width W2 (Metric)	9.0mm
	Height H (Imperial)	0.05"
	Height H (Metric)	1.3mm
	Height H2 (Imperial)	0.3"
	Height H2 (Metric)	7.5mm
	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.2"
	Bundle Diameter Max. (Metric)	31.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.03"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.04"
	Panel Thickness Min. (Metric)	0.75mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
	Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm
	Mounting Hole Diameter D Min. (Imperial)	0.26"
	Mounting Hole Diameter D Max. (Imperial)	0.28"
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS PA66HIRHS PA66HIRHS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987

150-52693

HellermannTyton

Logistic and Packaging	Content Unit (BMEcat)	pieces
	Weight (Metric)	2kg