

Part Number: 1508150 D Design B

RS485, 1 Pr #24 Str TC, PO Ins, OS+TC Brd, PVC Jkt, CM

Product Description

RS-485, 1 Pair 24AWG (7x32) Tinned Copper, PO Insulation, Overall Beldfoil®+Tinned Copper Braid(90%) Shield, PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:	RS-485, DMX-512
------------------------	-----------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
24	7x32	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1
Conductor Size:	24 AWG

Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.0225 in

Color Chart

Color	Gr[d]Y HndY
White/Blue & Blue/White	Š } * æ å ä æ Å

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum/Polyester	Beldfoil® with shorting fold	100 %	TC - Tinned Copper	24	7x32 mm
Braid	2	TC - Tinned Copper		90 %			

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.232 in	0.035 in

Construction and Dimensions

Cabling

Lay Direction	Twists	Filler
Left Hand	4.8 twist/ft	Fibrous Polypropylene

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
24 Ohm/1000ft	3.4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12.8 pF/ft	23 pF/ft

Impedance

Nominal Characteristic Impedance
120 Ohm

High Frequency (Nominal/Typical)

Nom. Insertion Loss
0.6 dB/100ft

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.6 ns/ft	66 %

Current

Element	Max. Recommended Current [A]
10C Temperature Rise	Per conductor @ 25°C Ambient (10C temperature rise): 2.1 A

Voltage

UL Description	UL Voltage Rating
Type CM	300 V RMS (UL type CM)
AWM 2919	30 V RMS (UL AWM 2919)

Electrical Characteristics Notes:	Attenuation @ 1 MHz: .6 dB/100 ft nominal
-----------------------------------	---

Temperature Range

UL Temp Rating:	80°C (UL AWM Style 2919)
Operating Temp Range:	-30°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	36 lbs/1000ft
Max Recommended Pulling Tension:	72.3 lbs
Min Bend Radius/Minor Axis:	2.5 in

Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
UL AWM Style:	2919 (30 V 80°C)
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes

Suitability

Suitability - Hazardous Locations:	Yes
Suitability - Indoor:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 (UL Loading)
CSA Flammability:	FT1

UL voltage rating:	300 V RMS (CM)
--------------------	----------------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

PRINT LEGEND:

DSM&T P/N 571X-SL9841 CM 1 PR 24 SHIELDED (UL) E108998 (-PLANT ID) OR AWM 2919
LOW VOLTAGE COMPUTER CABLE OR C(UL)CM – ROHS

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.