

151-00785



Article Number: 151-00785



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00785
Type CCFT6LG
Color Black (BK)

Features and Benefits The cable bundle is fastened to the winder bar with cable ties or adhesive tape. It is routed above the connector clip.
 The two TapeClip elements are used to clip connectors onto the cable set. The connector is fixed securely to the set and is protected against soiling. None of the elements are direction-specific.

Fixation Method (FF) Fir Tree

Product Dimensions

Panel Thickness Max. (Imperial)	0.16 "		
Panel Thickness Min. (Imperial)	0.03 "		
Mounting Hole Diameter D (Imperial)	0.24-0.26 "		
Mounting Hole Diameter D (Metric)	6.0 - 6.7 mm		
Mounting Hole Diameter D Min. (Imperial)	0.24 "		
		Mounting Hole Diameter D Max.0.26 "	
		(Imperial)	Mounting Hole Diameter D Max.6.7 mm
			(Metric) 6.0 mm
Mounting Hole Diameter D Min. (Metric)			

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 5000
Carton Quantity 5000 Pieces
Weight (Metric) 0.8 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut PA66HIRHS
Flammability UL94 HB
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1) Yes

