HellermannTyton

151-00932

	Article Number: 151-00932
~	Standoff Tape Clip, Panel Thickness 0.02" - 0.27", PA66HIRHS, Natural, 3,000/box
	Y ROHS
Download drawing	nload spec sheet

Base Data

Local Order Number	151-00932	
Туре	SOC11FTOVAL	
Color	Natural (NA)	
Features and Benefits	 Staggered fir tree branch design provides low insertion forces and high extraction forces. Initial fir tree serves as a locating feature for assistance in blind assembly applications. 	
Product Description	Bundling clips are designed to provide simple and easy methods of securing cable bundles, hoses, or pipes. They are fastened onto the tape bar using bundle or cable ties. The different fixing orientations allow tape clips to be used with a wide range of panel thicknesses and hole diameters. Standard bundling clips are available as well as standof and stud mount versions.	
Short Description	Standoff Tape Clip, Panel Thickness 0.02" - 0.27", PA66HIRHS, Natural, 3,000/box	

Product Dimensions

Mounting Hole Diameter D (Imperial)	
	0.24 x 0.48 "; 0.25 x 0.50 ", 0.25 x 0.5 " ;0.27 x 0.47 "
Panel Thickness Min. (Imperial)	0.02 "
Panel Thickness Max. (Imperial)	0.27 "
Height H (Metric)	21.0 mm
Height H (Imperial)	0.8 "
Length L2 (Metric)	20.0 mm
Length L2 (Imperial)	0.8 "
Length L (Metric)	50.0 mm
Length L (Imperial)	2.0 "

(Imperial)

Mounting Hole Diameter D Max.12.5 mm (Metric) 6.5 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per carton

Package Quantity (Metric) 3000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS compliant (Article 4 - 1) Yes

© HellermannTyton 2015