

Specification Sheet

Part Number: 151-03905



Bolt-down, one-piece design can bundle and secure two high-voltage cables inside convoluted tubing.
Integrated M6 Stud Mount acts as third hand for retention while attaching.
Compression limiter for high-torque bolted applications.
Releasable latch for serviceability.

Article Number	151-03905
Type	DHVC24M6
Color	Black (BK)
Quantity Per	carton
Product Description	These clamps separate multiple bundles and secure them to any surface with a 6 mm stud or bolt. The one-piece hinged design snaps together to keep bundles such as tubing or battery cables separated. The robust design and durable materials also make it ideal for heavy duty applications.
Short Description	HV Dual Clamp with M6 stud mount, .94" Bundle Dia, PA66HIRHSUV, Black, 250/ctn
Global Part Name	DHVC24M6-PA66HIRHSUV-BK

Length L (Imperial)	3.96
Length L (Metric)	100.5
Width W (Imperial)	1.20
Width W (Metric)	30.5
Bundle Diameter Max (Imperial)	0.94
Bundle Diameter Max (Metric)	24.0
Bundle Diameter 1st Loop Max (Imperial)	0.94
Bundle Diameter 1st Loop Max (Metric)	24.0
Bundle Diameter 2nd Loop Max (Imperial)	0.94
Bundle Diameter 2nd Loop Max (Metric)	24.0
Height H (Imperial)	1.26
Height H (Metric)	32.0
Mounting Hole Diameter D (Imperial)	0.24
Mounting Hole Diameter D (Metric)	M6

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	250
Package Quantity (Metric)	250
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)