

## Specification Sheet

Part Number: 151-01528



**Article Number**

151-01528

**Type**

FMB4APT-I

**Color**

White (WH)

**Features & Benefits**

- One base fits more surfaces – flat, curved and moderately angled – for versatile applications.
- High-strength, weather-resistant adhesive offers excellent performance indoors and out.
- 4-way opening allows parallel or perpendicular cable routing options.

**Quantity Per**

bag

**Product Description**

HellermannTyton FlexTack Adhesive Cable Tie Mounts deliver excellent mounting performance on flat, curved and moderately angled surfaces. Use in combination with 18- through 50-pound cable ties to provide stability when securing bundles. Excellent performance in extreme environmental conditions for a wide range of indoor and outdoor applications; on varnished, powder coated, metal or plastic surfaces; in electrical equipment; and where drilling a hole is not possible or desirable. The 4-way saddle allows cable ties to be inserted parallel or perpendicular to the wire bundles.

|                                       |                                                                                            |
|---------------------------------------|--------------------------------------------------------------------------------------------|
| <b>Short Description</b>              | Flexible Cable Tie Mounting Base, 1.1" x 1.1", 0.21" Max Tie Width, PA66HS, White, 100/pkg |
| <b>Global Part Name</b>               | FMB4APT-I-PA66HS-WH                                                                        |
| <b>Length L (Imperial)</b>            | 1.1                                                                                        |
| <b>Length L (Metric)</b>              | 28.0                                                                                       |
| <b>Fixation Method</b>                | Self-Adhesive                                                                              |
| <b>Width W (Imperial)</b>             | 1.1                                                                                        |
| <b>Width W (Metric)</b>               | 28.0                                                                                       |
| <b>Height H (Imperial)</b>            | 0.25                                                                                       |
| <b>Height H (Metric)</b>              | 6.3                                                                                        |
| <b>Cable Tie Width Max (Imperial)</b> | 0.213                                                                                      |
| <b>Cable Tie Width Max (Metric)</b>   | 5.4                                                                                        |
| <b>Material</b>                       | Polyamide 6.6 heat stabilized (PA66HS)                                                     |
| <b>Material Shortcut</b>              | PA66HS                                                                                     |
| <b>Adhesive</b>                       | Acrylate with base of acrylic foam                                                         |
| <b>Flammability</b>                   | UL 94 V2 (excluding adhesive)                                                              |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Halogen free</b>                   | Yes                               |
| <b>Adhesive Operating Temperature</b> | -40°F to +194°F (-40°C to +90°C)  |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C) |
| <b>Reach Complaint(Article 33)</b>    | Yes                               |
| <b>ROHS Complaint</b>                 | Yes                               |
| <b>Package Quantity(Imperial)</b>     | 100                               |
| <b>Package Quantity (Metric)</b>      | 100                               |
| <b>Customs Number</b>                 | 3926909988                        |
| <b>Content Unit(BMEcat)</b>           | pcs.                              |
| <b>Weight (Metric)</b>                | 0.17964                           |
| <b>Weight (Imperial)</b>              | 0.396                             |