

Specification Sheet

Part Number: 151-02094



Article Number

151-02094

Type

HDM320

Color

Black (BK)

Features & Benefits

- Mount and tie combination makes it easy to service bundles in the field.
- Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
- Eliminates the needs for multiple sized fix diameter clamps.

Quantity Per

carton

Product Description

The high-torque mount is designed for use with power-assisted impact wrenches and is molded with a heavy bushing to withstand the forces required to tighten grade 8 bolts. The arched H-profile of the saddle surface allows for a broad surface contact with the bundle, minimizing pinching and crushing of the bundles, and adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

Short Description

High Torque Mount, Mounting Hole Dia. 0.327", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 500/pkg

Global Part Name

HDM320-PA66HIRHSUV-BK

Length L (Imperial)

1.85

Length L (Metric)

47.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

1.0

Width W (Metric)

25.0

Height H (Imperial)

0.81

Height H (Metric)

20.7

Cable Tie Width Max (Imperial)

0.5

Cable Tie Width Max (Metric)

12.7

Mounting Hole Diameter D (Imperial)

0.327

Mounting Hole Diameter D (Metric)

8.31 mm

Mounting Hole Diameter D Min (Imperial)

0.327

Mounting Hole Diameter D Max (Imperial)

0.327

Mounting Hole Diameter D Max (Metric)

8.31

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Maximum Torque (kgf-cm)	1576.0
Maximum Torque (lbf-ft)	114.0
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.0202
Weight (Imperial)	0.0446

