

155-05800



Article Number: 155-05800

Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HIRHS, Black, 1,500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 155-05800

Type T50SOSFT6E

Color Black (BK)

Features and Benefits

- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.
- Disc feature provides anti-rattle protection in high vibration applications.

Product Description Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HIRHS, Black, 1,500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 150 N

Length L (Imperial) 6.0 "

Length L (Metric) 160 mm

Length of Fir Tree 8.4 mm

Width W (Imperial) 0.19 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.33 "

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.12 "

Panel Thickness Min. (Imperial) 0.03 "

Mounting Hole Diameter D (Imperial) 0.26 - 0.28 "

Mounting Hole Diameter D (Metric) 6.5 - 7.0 mm

Mounting Hole Diameter D Min. (Imperial) 0.26 "

Mounting Hole Diameter D Max. (Imperial) 0.28 "

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. (Metric) 7.0 mm

Mounting Hole Diameter D Min. (Metric) 6.5 mm

Thickness T (Metric) 1.35 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1500

Carton Quantity 6000 Pieces

Weight (Metric) 1.31 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes