

155-30602



Article Number: 155-30602

Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 155-30602

Type T50SSBS50TE

Color Black (BK)

- Features and Benefits**
- Design gives quick and easy assembly by hand without the need for tools.
 - Mount can be used in a wide variety of applications where 5mm weld studs or 5mm ISO bolts.
 - Design provides low insertion force and high extraction force.

Product Description The Standoff Stud Mount tie applies easily to weld studs and secures bundles away from fixing holes. These are used primarily in the automotive industry, but can be used in a variety of applications.

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 200 N

Length L (Imperial) 6.0 "

Length L (Metric) 160 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.0 mm

Bundle Diameter Min. (Imperial) 0.16 "

Bundle Diameter Min. (Metric) 4.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Stud Length Max. (Imperial) 0.65 "

Stud Length Max. (Metric) 16.5 mm

Thickness T (Imperial) 0.05 "

Thickness T (Metric) 1.35 mm

Stud Size (Imperial) 0.2 "

Stud Size (Metric) 5.0 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 500 Pieces
Carton Quantity 4000 Pieces
Weight (Metric) 2.3 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1) Yes