

156-00049



Article Number: 156-00049

Rotatable Cable Tie and Edge Clip, 6.3" Length, Outside Serrated, PA66HS, Black, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00049

Type CBT30MR

Color Black (BK)

- Features and Benefits**
- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
 - Edge Clip provides low insertion force and high extraction force ideal for assembly environments.
 - Cable tie is both rotatable and outside serrated to reduce bundle chafing.

Product Description The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

Fixation Method (FF) Edge Clips with tie

Identification Plate Position none

Variant Inside Serrated

Short Description Rotatable Cable Tie and Edge Clip, 6.3" Length, Outside Serrated, PA66HS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 30.0 lbs

Minimum Tensile Strength (Metric) 135 N

Length L (Imperial) 6.3 "

Length L (Metric) 160 mm

Length L2 (Imperial) 0.53 "

Length L2 (Metric) 13.5 mm

Width W (Imperial) 0.14 "

Width W (Metric) 3.5 mm

Cable Tie Width Max. (Imperial) 0.14 "

Cable Tie Width Max. (Metric) 3.5 mm

Width W2 (Imperial) 0.75 "

Width W2 (Metric) 19.0 mm

Height H (Imperial) 0.05 "

Height H (Metric) 1.2 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.3 "

Bundle Diameter Max. (Metric) 32.0 mm

Panel Thickness Max. (Imperial) 0.1 "

Panel Thickness Min. (Imperial) 0.04 "

Cable Tie Head Length (Imperial) 3.5 "

Logistics and Packaging

Quantity Per carton

Package Quantity (Metric) 500 Pieces

Carton Quantity 5000 Pieces

Weight (Metric) 4 kg

Material and Specifications

Material Polyacetal (POM)
Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS
POM

Material Cable Tie Polyamide 6.6 heat stabilized (PA66HS)

Material Edge Clip Polyacetal (POM)

Flammability UL94 HB

Operating Temperature -40°F to +194°F (-40°C to +90°C)

ROHS compliant (Article 4 - 1) Yes