

156-00070



Article Number: 156-00070

Heavy Duty Fir Tree with Cable Tie, 15.1" Length, Panel Thickness .04"-.26", PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 156-00070

**Type** WSRFT9A

**Color** Black (BK)

- Features and Benefits**
- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
  - Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
  - Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

**Product Description** HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

**Fixation Method (FF)** Fir Tree

**Identification Plate Position** none

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Heavy Duty Fir Tree with Cable Tie, 15.1" Length, Panel Thickness .04"-.26", PA66HIRHSUV, Black, 100/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 534 N

**Length L (Imperial)** 15.0 "

**Length L (Metric)** 380.0 mm

**Width W (Imperial)** 0.5 "

**Width W (Metric)** 12.7 mm

**Width W2 (Imperial)** 0.51 "

**Width W2 (Metric)** 13.0 mm

**Height H (Imperial)** 0.75 "

**Height H (Metric)** 19.1 mm

**Height H2 (Imperial)** 0.36 "

**Height H2 (Metric)** 9.0 mm

**Bundle Diameter Max. (Imperial)** 4.1 "

**Bundle Diameter Max. (Metric)** 105.0 mm

**Disc Diameter (Imperial)** 0.85 "

**Disc Diameter (Metric)** 21.6 mm

**Panel Thickness Max. (Imperial)** 0.26 "

Panel Thickness Min. (Imperial) 0.04 "

Mounting Hole Diameter D Min.  
(Imperial) 0.34 "

Mounting Hole Diameter D Max.0.36 "  
(Imperial)

Mounting Hole Diameter D Max.9.25 mm  
(Metric) 8.75 mm

Mounting Hole Diameter D Min. (Metric)

## Logistics and Packaging

---

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 500

## Material and Specifications

---

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -67°F to +212°F (-55°C to +100°C)

ROHS compliant (Article 4 - 1) Yes