

156-00072



Article Number: 156-00072

Heavy Duty Fir Tree with Cable Tie, 9" Length, Mount Hole Dia .04"-.62", PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00072

Type WSSFT9B

Color Black (BK)

- Features and Benefits**
- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
 - Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
 - Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

Product Description HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Fir Tree with Cable Tie, 9" Length, Mount Hole Dia .04"-.62", PA66HIRHSUV, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 534 N

Length L (Imperial) 9.0 "

Length L (Metric) 228.0 mm

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Width W2 (Imperial) 0.51 "

Width W2 (Metric) 13.0 mm

Height H (Imperial) 1.1 "

Height H (Metric) 28.5 mm

Height H2 (Imperial) 0.73 "

Height H2 (Metric) 18.4 mm

Bundle Diameter Max. (Imperial) 2.3 "

Bundle Diameter Max. (Metric) 57.0 mm

Disc Diameter (Imperial) 0.9 "

Disc Diameter (Metric) 21.6 mm

Panel Thickness Max. (Imperial) 0.62 "

Panel Thickness Min. (Imperial) 0.04 "

Mounting Hole Diameter D Min. (Imperial) 0.34 "

Mounting Hole Diameter D Max. (Imperial) 0.36 "

Mounting Hole Diameter D Max. (Metric) 9.25 mm
8.75 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 500

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -65°F to +212°F (-54°C to +100°C)

ROHS compliant (Article 4 - 1) Yes