

156-00156



Article Number: 156-00156

Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 156-00156

**Type** T50SFT6

**Color** Black (BK)

**Features and Benefits**

- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.
- Disc feature provides anti-rattle protection in high vibration applications.

**Product Description** Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

**Fixation Method (FF)** Fir Tree

**Identification Plate Position** none

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26"-.28", PA66HS, Black, 500/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 6.0 "

**Length L (Metric)** 160.0 mm

**Length L2 (Imperial)** 0.46 "

**Length L2 (Metric)** 11.6 mm

**Length L3 (imperial)** 0.54 "

**Length L3 (metric)** 13.8 mm

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Width W2 (Imperial)** 0.35 "

**Width W2 (Metric)** 9.0 mm

**Width W3 (Imperial)** 0.2 "

**Width W3 (Metric)** 5.0 mm

**Height H (Imperial)** 0.05 "

**Height H (Metric)** 1.2 mm

**Height H2 (Imperial)** 0.3 "

**Height H2 (Metric)** 7.5 mm

<b>Bundle Diameter Min. (Imperial)</b>	0.06 "
<b>Bundle Diameter Min. (Metric)</b>	3.0 mm
<b>Bundle Diameter Max. (Imperial)</b>	1.4 "
<b>Bundle Diameter Max. (Metric)</b>	35.0 mm
<b>Disc Diameter (Imperial)</b>	0.63 "
<b>Disc Diameter (Metric)</b>	16.0 mm
<b>Panel Thickness Max. (Imperial)</b>	0.12 "
<b>Panel Thickness Min. (Imperial)</b>	0.03 "
<b>Mounting Hole Diameter D (Imperial)</b>	0.26 - 0.28 "
<b>Mounting Hole Diameter D (Metric)</b>	6.5 - 7.0 mm
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.252 "
<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.28 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	7.0 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	6.5 mm
<b>Thickness T (Metric)</b>	1.2 mm

## Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500
<b>Carton Quantity</b>	3000

## Material and Specifications

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HIRHS PA66HS
<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Edge Clip</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS compliant (Article 4 - 1)</b>	Yes