

156-00264



Article Number: 156-00264

Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00264

Type T50SOSST6.5E-MDL

Color Black (BK)

- Features and Benefits**
- Arrowhead design makes installation quick and easy by hand.
 - Ties "clicks" into place upon final installation signaling installer insertion is complete.
 - Design provides low insertion and high extraction force.

Product Description Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Arrowhead Mount Ties with Seal, 6.3" Long, 50lb Tensile, PA66HS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 200 N

Length L (Imperial) 6.3 "

Length L (Metric) 158.8 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.67 "

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.2 "

Bundle Diameter Max. (Metric) 30.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.07 "

Panel Thickness Min. (Imperial) 0.02 "

Mounting Hole Diameter D (Imperial) 0.25 - 0.26 "

Mounting Hole Diameter D Min. 0.25 "

(Imperial) Mounting Hole Diameter D Max. 0.26 "
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 6.7 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 6.3 mm

Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 3000 Pieces

Weight (Metric) 1.51 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes