

156-00057



Article Number: 156-00057

Description: 2-Piece Cable Tie/Fir Tree Mount, 6.0"L, .26"-.28" Mounting Hole Diameter, PA66HIRHS, Black, 500/pkg

Base Data	
Local Order Number	156-00057
Type	T30RFT7
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
Quantity Per	bag
Product Description	Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.
GLOBAL PART NAME (auto set)	T30RFT7-PA66HS-BK
Short Description	2-Piece Cable Tie/Fir Tree Mount, 6.0"L, .26"-.28" Mounting Hole Diameter, PA66HIRHS, Black, 500/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	30.0lbs
Minimum Tensile Strength (Metric)	135N
Length L (Imperial)	6.0"
Length L (Metric)	150.0mm
Length L2 (Imperial)	0.46"
Length L3 (imperial)	0.8"
Length L3 (metric)	19mm
Fixation Method	Fir Tree
Identification Plate Position	none
Length L2 (Metric)	11.6mm
Releasable Closure	No
Tie Closure	plastic pawl

156-00057

HellermannTyton

Product Dimensions	Variant	Inside Serrated
	Width W (Imperial)	0.14"
	Width W (Metric)	3.5mm
	Width W2 (Imperial)	0.46"
	Width W2 (Metric)	11.6mm
	Width W3 (Imperial)	0.2"
	Width W3 (Metric)	5.0mm
	Height H (Imperial)	0.04"
	Height H (Metric)	1.1mm
	Height H2 (Imperial)	0.5"
	Height H2 (Metric)	12.7mm
	Bundle Diameter Min. (Imperial)	0.2"
	Bundle Diameter Min. (Metric)	4.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.28"
	Panel Thickness Max. (Metric)	7.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.8mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
	Mounting Hole Diameter D (Metric)	6.5 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.256"
	Mounting Hole Diameter D Max. (Imperial)	0.276"
Thickness T (Metric)	1.1mm	
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes

156-00057



Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987