

156-00861

HellermannTyton

Article Number: 156-00861

Description: Cable Tie & Edge Clip, Out. Serr., 8.0", EC4B, Panel Thick 1.0–3.0 mm, 50lb, PA66HS, Black, 500/bag



| Base Data | |
|-------------------------------------|--|
| Local Order Number | 156-00861 |
| Type | T50ROSEC4B |
| Color | Black (BK) |
| Features and benefits | <ul style="list-style-type: none"> • Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole. • Edge Clip provides low insertion force and high extraction force ideal for assembly environments. • Cable tie is outside serrated to reduce bundle chafing. |
| Quantity Per | bag |
| Product Description | The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing. |
| Global Part Name | T50ROSEC4B-PA66HS/PA66HIRHS-BK |
| Short Description | Cable Tie & Edge Clip, Out. Serr., 8.0", EC4B, Panel Thick 1.0–3.0 mm, 50lb, PA66HS, Black, 500/bag |
| Product Dimensions | |
| Minimum Tensile Strength (Imperial) | 50.0lbs |
| Minimum Tensile Strength (Metric) | 225N |
| Length L (Imperial) | 8.0" |
| Length L (Metric) | 200.0mm |
| Length L2 (Imperial) | 0.55" |
| Fixation Method | EdgeClip, top, assembled, 2 piece |
| Identification Plate Position | none |
| Length L2 (Metric) | 14.0mm |
| Releasable Closure | No |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.18" |
| Width W (Metric) | 4.6mm |

156-00861



| | | |
|-----------------------------|---------------------------------|---|
| Product Dimensions | Width W2 (Imperial) | 0.45" |
| | Width W2 (Metric) | 11.5mm |
| | Height H (Imperial) | .05" |
| | Height H (Metric) | 1.30mm |
| | Height H2 (Imperial) | .43" |
| | Height H2 (Metric) | 10.92mm |
| | Bundle Diameter Min. (Imperial) | 0.16" |
| | Bundle Diameter Min. (Metric) | 4.0mm |
| | Bundle Diameter Max. (Imperial) | 1.8" |
| | Bundle Diameter Max. (Metric) | 45.0mm |
| | Panel Thickness Max. (Imperial) | 0.12" |
| | Panel Thickness Max. (Metric) | 3.0mm |
| | Panel Thickness Min. (Imperial) | 0.04" |
| | Panel Thickness Min. (Metric) | 1.0mm |
| | Thickness T (Imperial) | 0.05" |
| | Thickness T (Metric) | 1.2mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS) |
| | Material Shortcut | PA66HS PA66HIRHS |
| | Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |
| | Flammability | UL 94 HB |
| | Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 500 |
| | Package Quantity (Metric) | 500 |
| | Customs Number(Schedule B) | 3926909987 |
| | Weight (Metric) | 4.5kg |