

157-00072

Article Number: 157-00072

Fir Tree with Tie, 6.4" Long, Mounting Hole Diameter .30"-.33", PA66HS, Black, 1,000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 157-00072

Type T50SOSFT8E

Color Black (BK)

Features and Benefits

- Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.
- Initial fir tree serves as a locating feature for assistance in blind assembly applications.
- Disc feature provides anti-rattle protection in high vibration applications.

Product Description Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The design also provides low insertion and high extraction force.

Fixation Method (FF) Fir Tree

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Fir Tree with Tie, 6.4" Long, Mounting Hole Diameter .30"-.33", PA66HS, Black, 1,000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.4 "

Length L (Metric) 163.0 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.43 "

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.02 "

Panel Thickness Min. (Imperial) 0.02 "

Mounting Hole Diameter D (Imperial) 0.3 - 0.33 "

Mounting Hole Diameter D (Metric) 8.0 - 8.5 mm

Mounting Hole Diameter D Min. 0.31 "
(Imperial)

Mounting Hole Diameter D Max. 0.33 "
(Imperial)

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. 8.5 mm
(Metric)

Mounting Hole Diameter D Min. (Metric) 8.0 mm

Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000 Pieces

Carton Quantity 5000 Pieces

Weight (Metric) 1.547 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

ROHS compliant (Article 4 - 1) Yes