

157-00106



Article Number: 157-00106

Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, Without Thumb Bar, PA66HS, Black, 1000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 157-00106

Type T50SOSB5-High-E-O-US

Color Black (BK)

Features and Benefits

- Head allows for a .2" lateral adjustment on stud during installation.
- Quick and easy installation ideal for manufacturing environment.

Product Description Oval Shaped Stud Mount's special design allows for a .2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Short Description Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, Without Thumb Bar, PA66HS, Black, 1000/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.6 "

Length L (Metric) 167.0 mm

Width W (Imperial) 0.2 "

Width W (Metric) 5.0 mm

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Stud Size (Imperial) 0.2 "

Stud Size (Metric) 5.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS compliant (Article 4 - 1) Yes