

157-00108



Article Number: 157-00108

Fir Tree Push Mount, 6.3" Long, Panel Thicknesses .02"-.17", Black, PA66HS, 1000/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 157-00108

**Type** T50SOSFT6E2

**Color** Black (BK)

- Features and Benefits**
- Fir Tree Push Mount offers simple and easy to use method of bundling and fixing cable ties.
  - The design of the fir tree ensures a positive secure fixing into panels with thicknesses from 0.6mm to 4.2mm or threaded blind holes.
  - The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

**Product Description** Fir Tree Push Tie designed for fixing cable harnesses. Their simplicity and ease of use make them an option for anywhere where secure and easy installation are needed.

**Fixation Method (FF)** Fir Tree

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Tie Closure** plastic pawl

**Short Description** Fir Tree Push Mount, 6.3" Long, Panel Thicknesses .02"-.17", Black, PA66HS, 1000/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 40.0 lbs

**Minimum Tensile Strength (Metric)** 180 N

**Length L (Imperial)** 6.3 "

**Length L (Metric)** 160.0 mm

**Length L2 (Imperial)** 0.35 "

**Length L2 (Metric)** 8.9 mm

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Bundle Diameter Min. (Imperial)** 0.04 "

**Bundle Diameter Min. (Metric)** 1.0 mm

**Bundle Diameter Max. (Imperial)** 1.4 "

**Bundle Diameter Max. (Metric)** 35.0 mm

**Disc Diameter (Imperial)** 0.63 "

**Disc Diameter (Metric)** 16.0 mm

**Panel Thickness Max. (Imperial)** 0.17 "

**Panel Thickness Min. (Imperial)** 0.02 "

**Mounting Hole Diameter D (Imperial)** 0.24 - 0.275 "

**Mounting Hole Diameter D (Metric)** 6.3 - 7.0 mm

**Mounting Hole Diameter D Min. (Imperial)** 0.248 "

**Mounting Hole Diameter D Max. (Imperial)** 0.275 "

**Mounting Hole Diameter D Max. (Metric)** 7.0 mm  
6.3 mm

**Mounting Hole Diameter D Min. (Metric)**

## Logistics and Packaging

---

**Quantity Per** bag

**Package Quantity (Metric)** 1000

## Material and Specifications

---

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS compliant (Article 4 - 1)** Yes