

157-00108

# HellermannTyton

Article Number: 157-00108



Description: 1-Piece Cable Tie/Fir Tree Mount With Disc, 6.3"L, 6.3–7.0 mm Mounting Hole, PA66HS, Black, 1000/pkg

Base Data	
Local Order Number	157-00108
Type	T50SOSFT6-E2
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> <li>• Fir Tree Push Mount offers simple and easy to use method of bundling and fixing cable ties.</li> <li>• The design of the fir tree ensures a positive secure fixing into panels with thicknesses from 0.6mm to 4.2mm or threaded blind holes.</li> <li>• The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</li> </ul>
Quantity Per	bag
Product Description	Fir Tree Push Tie designed for fixing cable harnesses. Their simplicity and ease of use make them an option for anywhere where secure and easy installation are needed.
Global Part Name	T50SOSFT6-E2-PA66HS-BK
Short Description	1-Piece Cable Tie/Fir Tree Mount With Disc, 6.3"L, 6.3–7.0 mm Mounting Hole, PA66HS, Black, 1000/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	40.0lbs
Minimum Tensile Strength (Metric)	180N
Length L (Imperial)	6.3"
Length L (Metric)	160.0mm
Length L2 (Imperial)	0.35"
Fixation Method	Fir Tree
Identification Plate Position	none
Length L2 (Metric)	8.9mm
Releasable Closure	No
Tie Closure	plastic pawl
Width W (Imperial)	0.18"
Width W (Metric)	4.6mm

157-00108



Product Dimensions	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.17"
	Panel Thickness Max. (Metric)	4.2mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Imperial)	0.24 - 0.275"
	Mounting Hole Diameter D (Metric)	6.3 - 7.0 mm
	Mounting Hole Diameter D Min. (Imperial)	0.248"
	Mounting Hole Diameter D Max. (Imperial)	0.275"
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS)
	Material Shortcut	PA66HS
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987