

157-00119



Article Number: 157-00119

Off-Set Fir Tree Cable Tie, 9.0" Long, 50lb, Mounting Diameter .24" - .28", PA66HIRHS, Grey, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 157-00119

Type T50ROSFT6SO25A

Color Gray (GY)

- Features and Benefits**
- One-piece cable tie and fixing offers a simple and easy to use method of bundling and fixing cables, through the design of the fir tree by ensuring positive and secure fixing into panels with thicknesses from 0.6-6.65mm.
 - The offset on the cable tie creates an alternate solution when an offset fixing option is required and a tape clip cannot be used due to the design which reduces the potential of the bundle flexing or shifting.
 - The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Product Description HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes.

The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Short Description Off-Set Fir Tree Cable Tie, 9.0" Long, 50lb, Mounting Diameter .24" - .28", PA66HIRHS, Grey, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 222.0 N

Length L (Imperial) 9.0 "

Length L (Metric) 230.0 mm

Fixation Method Fir Tree

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Height H (Imperial) 0.9 "

Height H (Metric) 21.2 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 2.0 "

Bundle Diameter Max. (Metric) 50.0 mm

Panel Thickness Max. (Imperial) 0.26 "

Panel Thickness Max. (Metric) 6.65 mm

Panel Thickness Min. (Imperial) 0.02 "

Panel Thickness Min. (Metric) 0.6 mm

Mounting Hole Diameter D (Imperial) 0.2-0.27 "

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 500

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut PA66HIRHS
Flammability UL94 V2
ROHS Compliant Yes