

157-00140

Article Number: 157-00140

Description: 1-Piece Cable Tie/Fir Tree Mount With Disc, 6.7"L, .24"-.27" Mounting Hole, PA66HIRHS, Black, 500/pkg



Base Data	Local Order Number	157-00140
	Type	T50SOSFT6LG-E2
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.</li> <li>• Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.</li> <li>• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.</li> </ul>
	Quantity Per	bag
	Product Description	<p>HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes.</p> <p>The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</p>
	Global Part Name	T50SOSFT6LG-E2-PA66HIRHS-BK
	Short Description	1-Piece Cable Tie/Fir Tree Mount With Disc, 6.7"L, .24"-.27" Mounting Hole, PA66HIRHS, Black, 500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		180N
Length L (Imperial)		6.7"
Length L (Metric)		167.0mm
Fixation Method		Fir Tree
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Width W (Metric)		4.6mm
Height H (Imperial)		.60"
Height H (Metric)		16.10mm

157-00140



Product Dimensions	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.3"
	Panel Thickness Max. (Metric)	8.25mm
	Panel Thickness Min. (Imperial)	0.02"
	Panel Thickness Min. (Metric)	0.6mm
	Mounting Hole Diameter D (Metric)	6.1 - 6.6 mm (hexagonal)
	Mounting Hole Diameter D Min. (Imperial)	0.24"
	Mounting Hole Diameter D Max. (Imperial)	0.27"
	Thickness T (Metric)	1.3mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Flammability	UL 94 V2
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces