			DATE	REV	ECN	DESCRIPTION
<u>PRODUCT</u>	<u>SPECIFICATION</u>		5/11/2004	А	4889	SPECIFICATION CREATED
	F14074- <u>14 19/.0147 TC AWM 1569 or 1581 TR-64 or</u> <u>AWM I A/B OD 0.102"</u> <u>19/.0147 TC LHL</u>	DIAMETER: 0 TOLERANCE ± : ±		<u>02</u>		MIN AVG WALL: 0.015
	UL: AWM 1569 or 1581 CSA: TR-64 or AWM	I A/B				MINIMUM WALL: 0.013
		<u></u>				<u></u>
Insulation:	<u>PVC</u>					
<u>Print Legend:</u>	<u>14 AWG (2.08mm2) E57498 (PLANT ID CODE) (AWM LOGO) AWM 1569 105C OR 1581 80C 300V VW-1 156205 CSA TR-64 90C FT1 OR AWM I A/B 105C 300V FT1</u>					
<u>Voltage:</u>	<u>300V</u>					
<u>Temperature:</u>	<u>1569=105C, 1007=80C, TR64=90C</u>					
<u>Notes:</u>						
This product complies with European Directive 2011/65/EU (RoHS 2) The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.						
This specification is pair without written conser	roprietary intellectual property of Coleman Cable. Any information cont of Coleman Cable.	ontained herein shall not be	e disclosed to	any party	CO	LEMAN CABLE, INC
<u>Customer Appro</u>	<u>oval:</u> t Nbr(s):					nields Drive gan, IL 60085
	Date:					200, 11, 60085 1-800-323-9355
	Company I					emancable.com