			DATE	REV	ECN	DESCRIPTION
<u>PRODUCT</u>	<u>SPECIFICATION</u>		11/24/2008	А	20782	SPECIFICATION CREATED
Stranding:	F14075- <u>14 41/30 TC AWM 1569 or 1581 TR-64 or</u> <u>AWM I A/B OD 0.111"</u> <u>41/30 TC LHL</u>	DIAMETER: (TOLERANCE ± : (TIN AVERAGE WALL: 0.015
<u>Style:</u>	UL: AWM 1569 or 1581 CSA: TR-64 or AWM	<u>I A/B</u>				<i>MINIMUM WALL:</i> <u>0.013</u>
<u>Insulation:</u> <u>Print Legend:</u>	PVC <u>14 AWG (2.08mm2) E96824 (PLANT ID CODE) (AWM LOGO) AWM 1569 105C OR 1581 80C 300V VW-1 156016 CSA TR-64 90C FT1 OR</u> <u>AWM I A/B 105C 300V FT1</u>					
<u>Voltage:</u> <u>Temperature:</u>	<u>300V</u> <u>1569=105C, 1581=80C, TR-64=90C</u>					
Notes:						
This product complies with European Directive 2011/65/EU (RoHS 2) The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.						
This specification is p without written conser	roprietary intellectual property of Coleman Cable. Any information c nt of Coleman Cable.	contained herein shall not be	e disclosed to	any party	CO	LEMAN CABLE, INC
<u>Customer Appro</u> Customer Part					1530 Sh Waukeg	nields Drive gan, IL 60085 1-800-323-9355
	Company	Name:				emancable.com