



### Specifications

- 5 mini coax, 28AWG, 75Ω
- Connector OD: 0.50"
- Cable OD: 0.32"
- 100% factory tested

### Standards

- UL Rated CMP and CMR
- Patch cord cable: UL Rated CM
- UL Listed: 1863



45° Connection  
15A6P1



8-Pin Cable Run  
VGA36P05BK



Keystone Snap Fit  
SFAVCT



15-Pin VGA Patching Run  
AV15M05



OPTISOK®  
CCPS1

### VGA Plug-n-Play X-End Connections

Female X-End 8-pin to female 15-pin		
Description	Single Pack	10-pack
Straight 180°	<b>15S6P1</b>	<b>15S6P10</b>
Angled 45°	<b>15A6P1</b>	<b>15A6P10</b>
Angled 90°	<b>15N6P1</b>	<b>15N6P10</b>
8" tail	<b>15T6P1</b>	<b>15T6P10</b>
Female X-End 8-pin to male 15-pin		
8" tail plenum	<b>15MP6P1</b>	<b>15MP6P10</b>

### AV Plug-n-Play X-End Horizontal Cable Runs

Male X-End 8-pin, black	
Description	Catalog No.
Non-plenum, 8-pin	<b>VGA6yyBK</b>
Plenum, 8-pin	<b>VGA6PyyBK</b>
Male X-End 8-pin to male 3.5mm, black	
Non-plenum, 8-pin, with 3.5mm	<b>VGA36yyBK</b>
Plenum, 8-pin, with 3.5mm	<b>VGA36PyyBK</b>

**yy** = Length: **15** (15'), **25** (25'), **35** (35'), **50** (50'), **75** (75'), and **100** (100'). Contact Hubbell customer service for custom lengths; minimum quantities and lead times may apply.

### OPTISOK®

OPTISOK pulling grip contains and protects the X-End connector bundle and saves time and labor by making job easier while protecting the connectors from possible damage during the pull. The OPTISOK has been designed to pull cables through conduits, plenums, under-floor duct, office partitions and raised access floors.

Bundle Size Range	Catalog No.
0.125–0.562"	<b>CCPS1</b>
0.250–0.750"	<b>CCPS2</b>

### X-End Keystone Snap Fit Connectors

Female keystone 8-pin to female X-End 8-pin, black	
Description	Catalog No.
Keystone, 4" tail	<b>SFAVCT</b>

### X-End AV Plug-n-Play Application Patching Runs

Male connector tail to male X-End 8-pin	
Description	Catalog No.
15-Pin VGA	<b>AV15Myy</b>
15-pin VGA with 3.5mm audio	<b>AV1535yy</b>

**yy** = Length: **05** (5'), **10** (10').