


DGC DATA GUIDE CABLE

Electronic and Electrical Wire & Cable Products

232 Sherman Street Gardner, MA 01440
 Phone: 978-632-0900 Fax: 978-630-1872
 Visit us on our website; www.dataguidecable.com



**2 CONDUCTORS 16 AWG UNSHIELDED
 PVC-TPU 80C 300V**

CONDUCTOR:

- 16 AWG (26x30) Tinned Annealed Copper Insulated with .010" Nominal Wall of PVC to a Nominal O.D. of .080" +/- .002"
- 2 Conductor Total
- Color Coded as Indicated

NOTES:

- Assembly Cabled with 2-5/8" Nominal Left Hand Direction Lay
- .001" Nominal Tissue Tape Pulled under Jacket
- .030" Minimum Average Wall Thickness Black "Pressure" TPU Jacket to .235" Nominal Final Diameter +/- .005"
- 12.5% Coverage Red Longitudinal Integral Jacket Stripe
- Printed in White Ink: " AWM 20233 80C 300V E90298 - - LL91737 CSA AWM I/II A/B 80C 300V FT1 XXXXXX FT"
- Sequential Footage Every 2 Feet (XXXXXX FT)

COLOR CODE

CONDUCTOR	COLOR
1	BLACK
2	RED

AGENCY APPROVAL

- UL AWM 20233 80C 300VOLTS
- CSA AWM 80C 300VOLTS FT1
- RoHS

REVISION HISTORY

0	1/15/14	WD	INITIAL RELEASE

Customer Number	0107-0020
D.G. Part Number	14A2-8
Prepared By:	KAM
Reviewed By:	WJD