

# ***CABLE USA***

*High Temperature Custom Engineered Cables*

## **PRODUCT DATA SHEET**

<b>TO:</b>		<b>FROM:</b>	CUSA
<b>COMPANY:</b>	IEWC	<b>ENG. BY:</b>	2C16AMTF
<b>PHONE:</b>		<b>DATE:</b>	3/16
<b>FAX:</b>		<b>PAGE</b>	1

---

<b>CABLE USA PART NUMBER:</b>	381602S5
<b>CUSTOMER PART NUMBER:</b>	N/A
<b>CONDUCTORS:</b>	<b>SIZE:</b> 16
	<b>STRANDING:</b> 19
	<b>MATERIAL:</b> TPC
<b>INSULATION MATERIAL:</b>	TEFZEL
<b>INSULATION THICKNESS (NOM):</b>	.0135"
<b>NUMBER OF CONDUCTORS:</b>	2
<b>CONDUCTOR COLOR CODE:</b>	1-GREEN, 1-VIOLET
<b>TYPE OF SHIELD/COVERAGE:</b>	FOIL SHIELD
<b>DRAIN WIRE:</b>	18 STRANDED TPC
<b>JACKET MATERIAL:</b>	TEFZEL
<b>JACKET THICKNESS (NOM):</b>	.020"
<b>JACKET COLOR:</b>	CLEAR
<b>MARKINGS METHOD/LEGEND:</b>	N/A
<b>FINISHED DIAMETER (NOM):</b>	.210"
<b>MAXIMUM OPERATING VOLTAGE:</b>	300V
<b>MAXIMUM OPERATING TEMPERATURE:</b>	-60°C TO +150°C
<b>AGENCY APPROVALS:</b>	N/A
<b>SPECIAL NOTES:</b>	VW-1