

232 Sherman Street Gardner, MA 01440 Phone: 978-632-0900 Fax: 978-630-1872 Visit us on our website; www.dataguidecable.com


3 CONDUCTORS 16 AWG UNSHIELDED TPU JACKET 80C 300VOLT

CONDUCTORS:

- 16 AWG (26x30) Tinned Annealed Copper Insulated with .009" Nominal Wall of PVC to a Nominal O.D. of .080" +/- .002"
- 3 Conductors Total
- Color Coded as Indicated

NOTES:

- .001" Nominal Thickness Tissue Separator Tape Pulled under Jacket
- .035" Nominal Wall Thickness Black Polyurethane "Pressure" Jacket to .245" Nominal Final Diameter +/- .005"
- Surface Printed in White Ink to UL AWM and CSA AWM as Follows: "E90298 AWM 20233 80C 300V - - LL91737 CSA AWM I/II A/B 80C 300V FT1"



COLOR CODE

CONDUCTOR	COLOR		
1	WHITE		
2	RED		
3	BLACK		

AGENCY APPROVAL

- RoHS APPROVED CONSTRUCTION

REVISION HISTORY

		0	5/8/13	WD	INITIAL RELEASE
Customer Number					
D.G. Part Number 13E	E1-7				
Prepared By: KAM					
Reviewed By: WJD					