

OLYMPIC WIRE & CABLE CORP.

Toll-Free (800) 526-2269

Fax (973) 227-1606

PRODUCT DATA SHEET

PART NUMBER: 81073/1

Issued: Tuesday, January 17, 2012

CABLE TYPE: FLEXIBLE CONTROL, UV RESISTANT

CABLE CONSTRUCTION:

NUMBER OF CONDUCTORS: 3
NUMBER OF PAIRS:
GAUGE: 16
STRANDING: 19/.0117

CONDUCTOR TYPE:

NICKEL PLATED COPPER:
BARE COPPER:
TINNED COPPER: X
SILVER PLATED COPPER:
ALLOY TYPE:
COPPER CLAD STEEL:
INSULATION MATERIAL: PVC
DIELECTRIC OD INCHES:
INSULATION THICKNESS: .016 INCHES
COLOR CODE 1: BROWN, BLUE, GREEN/YELLOW

COLOR CODE 2:

FILLER:

BARRIER:

SHIELD:

ARMOR:

DRAIN WIRE:

UL STYLE: 2464, CM

MILITARY SPEC:

FLAME TEST: VW-1, FT-4

RoHS COMPLIANT: YES

PRINT LEGEND:

PERFORMANCE:

DC RESISTANCE: OHMS PER MFT AT 20 C
CAPACITANCE: PF PER FT NOM AT 1 KHZ
IMPEDENCE: OHMS + - 15% FROM 1-20 MHZ
NOMINAL VEL OF PROP:
CE COMPLIANT: YES

ATTENUATION MAX DB PER 100 FEET:

MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:
MHZ:	DB:

FEATURE

NOTES:

RIP CORD: YES

JACKET MATERIAL: PVC

JACKET THICKNESS: .032 INCHES

JACKET COLOR: GREY

NOMINAL O.D.: .263 INCHES

CSA STYLE:

NEC TYPE:

OPERATING TEMPERATURE: -30 C + 105 C

VOLTAGE 300

WEIGHT PER 1000FT: 48 LBS

CHINESE RoHS COMPLIANT:

BEND RADIUS:

CA PROP 65 (CJ FOR WIRING & CABLE):