

232 Sherman Street Gardner, MA 01440
 Phone: 978-632-0900 Fax: 978-630-1872
 Visit us on our website; www.dataguidecable.com

3 CONDUCTOR SHIELDED TPE-TPU 80C 600VOLTS

CONDUCTORS:

- 16 AWG (26x30) Tinned Annealed Copper Insulated With .022" Wall of TPE to a Nominal O.D. of .103"
- 3 Conductor Total

COLOR CODE:

- As Indicated

NOTES:


- 3" Nominal Left Hand Direction Cable Lay
- Overall .0012" Thickness Aluminum/Polyester Tape Shield, Foil Facing Out
- 16 AWG 7 Strand Tinned CU Drain over Tape Shield
- Overall 75% Nominal Coverage 36 AWG Tinned Copper Braid Shield
- Overall .0015" Thickness Tissue Separator Tape under Jacket
- Overall .050" Nominal Wall Yellow Polyurethane Jacket to .352" +/- .015" Final Diameter
- Surface Printed in Black Ink:
 "E90298 AWM 20234 80C 600V VW-1 - - L91737 CSA AWM I/II A/B 80C 600V FT1"

ELECTRICALS

- DCR at 20C: 4.34 OHMS/1000'
- Dielectric Withstand: 1.2 KVAC for 1 Minute

MECHANICAL:

- Operating Temp: -50C to +80C
- Min. Bend Radius: 8 Times Cable Diameter



COLOR CODE

CONDUCTOR	COLOR
1	BLACK
2	WHITE
3	RED

AGENCY APPROVAL

- UL AWM 20234 80C 600VOLTS
- CSA AWM FT1 80C 600VOLTS
- RoHS COMPLIANT

REVISION HISTORY

0	3/09/2012	WD	FIRST ISSUE
1	4/12/13	WD	PRINT LEGEND – BEND RADIUS
2	5/17/13	WD	REMOVE KOMATSU LEGEND
3	8/8/13	WD	BARE TO TIN CU CONDRS

Customer Number	LW086-63
D.G. Part Number	12C7-5
Prepared By:	KAM
Reviewed By:	WJD