


Sizes continued on next page.

PART NUMBER	CORES	NOMINAL OD	LBS/MFT	KG/KM
2002002	2	0.201" / 5.1mm	31	46
2002003	3	0.209" / 5.3mm	38	57
2002004	4	0.224" / 5.7mm	47	70
2002005	5	0.252" / 6.4mm	62	93
2002007	7	0.295" / 7.5mm	85	127
2002012	12	0.362" / 9.2mm	119	177
2002018	18	0.437" / 11.1mm	190	284
2002025	25	0.528" / 13.4mm	243	363
2002034	34	0.594" / 15.1mm	327	487
2002041	41	0.626" / 15.9mm	386	575
2001802	2	0.213" / 5.4mm	39	58
2001803	3	0.224" / 5.7mm	49	73
2001804	4	0.252" / 6.4mm	52	77
2001805	5	0.276" / 7.0mm	80	119
2001807	7	0.327" / 8.3mm	111	165
2001812	12	0.406" / 10.3mm	166	247
2001818	18	0.476" / 12.1mm	239	356
2001818	18	0.587" / 14.9mm	334	498
2001825	25	0.587" / 14.9mm	334	498
2001834	34	0.654" / 16.6mm	369	550
2001841	41	0.705" / 17.9mm	402	600
2001850	50	0.791" / 20.1mm	470	700
2001702	2	0.224" / 5.7mm	44	65
2001703	3	0.236" / 6.0mm	56	84
2001704	4	0.268" / 6.8mm	76	113
2001705	5	0.291" / 7.4mm	92	137
2001707	7	0.346" / 8.8mm	129	192
2001712	12	0.425" / 10.8mm	198	295
2001718	18	0.516" / 13.1mm	282	420
2001725	25	0.622" / 15.8mm	402	600
2001734	34	0.701" / 17.8mm	521	777
2001741	41	0.760" / 19.3mm	621	926
2001750	50	0.835" / 21.2mm	732	1092

Robotic & C-Track Cable

- BENDING RADIUS: 7.5 X Cable Diameter
- TEMPERATURE: -5° C to +70° C. (Flame protection to IEC 60332.1)
- RATED WORKING VOLTAGE: 300/500V.
- STRANDING: VDE 0295 Class 6 - IEC 60228 (extra-fine bare copper)
- COLOR CODE: VDE-2093 - Black Cores / White Numbers & Green/Yellow Ground.
- APPROVALS: VDE-0281, CE Low-Voltage Directive & ROHS Compliant.



EXTRAFLEX is a high flex, heavy-duty, oil-resistant gray PVC insulated and jacketed continuous flex multi-conductor cable. These cables are ideal for use in robotics and machine production and drag chains where high flexibility is essential. Applications include gantry robots, cable tracks, pick & place units, automated handling equipment, machine tools and conveyor systems.



EXTRAFLEX

The Mueller Group, Inc.

EXTRAFLEX



The Mueller Group, Inc.

EXTRAFLEX Sizes Continued.

- BENDING RADIUS: 7.5 X Cable Diameter
- TEMPERATURE: -5° C. to +70° C. (Flame protection to IEC 60332.1)
- RATED WORKING VOLTAGE: 300/500V.
- STRANDING: VDE 0295 Class 6 - IEC 60228 (extra-fine bare copper)
- COLOR CODE: VDE-Z093 - Black Cores w/ White Numbers & Green/Yellow Ground.
- APPROVALS: VDE-0281, CE Low-Voltage Directive & ROHS Compliant

PART NUMBER	CORES	NOMINAL OD	LBS/MFT	ICG/KM
2001602	2	0.252" / 6.4mm	61	91
2001603	3	0.268" / 6.8mm	78	117
2001604	4	0.291" / 7.4mm	99	147
2001605	5	0.327" / 8.3mm	121	181
2001607	7	0.390" / 9.9mm	183	273
2001612	12	0.476" / 12.1mm	262	391
2001618	18	0.571" / 14.5mm	396	590
2001625	25	0.701" / 17.8mm	537	801
2001634	34	0.776" / 19.7mm	727	1084
2001641	41	0.843" / 21.4mm	865	1290
2001650	50	0.933" / 23.7mm	1020	1521
2001665	65	1.087" / 27.6mm	1337	1994
2001402	2	0.303" / 7.7mm	87	130
2001403	3	0.331" / 8.4mm	107	160
2001404	4	0.358" / 9.1mm	134	200
2001405	5	0.402" / 10.2mm	180	269
2001407	7	0.480" / 12.2mm	239	357
2001412	12	0.598" / 15.2mm	384	572
2001418	18	0.713" / 18.1mm	537	800
2001425	25	0.886" / 22.5mm	738	1100
2001434	34	0.992" / 25.2mm	1006	1500
2001441	41	1.079" / 27.4mm	1207	1800
2001450	50	1.185" / 30.1mm	1409	2100
12 AWG (224/34) 4.0mm ²	3	0.409" / 10.4mm	148	221
2001203	4	0.449" / 11.4mm	174	260
2001204	4	0.501" / 12.7mm	213	318
2001205	5	0.524" / 13.3mm	263	392
10 AWG (192/32) 6.0mm ²	4	0.571" / 14.5mm	326	481
2001004	4	0.697" / 17.7mm	431	642
2000804	4	0.776" / 19.7mm	523	780
2000805	5	0.780" / 19.8mm	621	926
6 AWG (512/32) 16.0mm ²	4	0.878" / 22.3mm	761	1135
2000605	5			

* Additional sizes may be available.