



Product Specification Sheet

1780 Birchwood Avenue
Des Plaines, Illinois, 60018
Ph: 847-299-9299 Fx: 847-299-9298
www.isotecwire.com
www.sheersoundcable.com

ISOTEC PART/QUOTE NUMBER: X347029-50
CUSTOMER PART NUMBER:

DESCRIPTION: 16 AWG 10 CONDUCTORS 26/30 TINNED COPPER, .020" PVC, OVERALL .028" PVC JACKET RISER GRAY CMG, CMR C(UL)US OR (UL) CL3R FT4

CONDUCTOR/PAIR COUNT:	10 CONDUCTORS	JACKET THICKNESS:	.028"
GAUGE & STRANDING:	16 AWG 26/30	JACKET COLOR:	GRAY
D.C. RESISTANCE:	4.0 Ω/MFT	JACKET MATERIAL:	PVC
PRIMARY INSULATION TYPE:	PVC	RIPCORD:	YES
INSULATION THICKNESS:	.020"	NOMINAL O.D.:	.464"
COLOR CODE:	See Notes*	VOLTAGE RATING:	300V
SHIELD:	N/A	TEMP. RATING:	60C
TAPE:	N/A	UL TYPE OR STYLE:	CMG, CMR OR CL3R
DRAIN WIRE:	N/A	PACKAGING:	TBA
CAP. COND TO COND.:	N/A	COPPER WEIGHT:	83.99 LBS/MFT
CAP. COND TO SHIELD:	N/A	SHIPPING WEIGHT:	154 LBS/MFT
FOOTAGE MARKERS:	ASCENDING & DESCENDING		
PRINT LEGEND:	ISOTEC, INC. 16 AWG CMG, CMR C(UL)US OR (UL) CL3R FT4		

NOTES: Shipping Tolerance: +/- 10%
Length Tolerance: +/- 10%
Random/Odd Length Tolerance: May ship up to 15% of order total on random/odd lengths.
*Color Code: Black, White, Red, Green, Brown, Blue, Orange, Yellow, Purple, Gray.
All wall thickness and diameter as well as electrical information is nominal.

ACCEPTANCE OF ABOVE DESIGN: _____ **DATE:** _____

Isotec makes every effort to provide accurate specifications. Printing errors are subject to correction.
Standard product specifications are subject to change without notice. Contact your Isotec sales person for current specifications.
Material will not be release to production until sign spec is confirm.

