



ATLAS WIRE LLC.
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#16 19/29 TC .017" PVC
RoHS COMPLIANT

MIL-DTL- 16878/2 TYPE C 105c – 1000v OR
MIL -W-76D TYPE MWP 90c – 1000v

CONDUCTOR:	#16 19/29 TINNED COPPER ¾" UNILAY
	APPROXIMATE NOMINAL O.D. .057"
	APPROXIMATE CIRCULAR MILL AREA 2,409
	WEIGHT PER THOUSAND FEET 7.50#
	BASIC SPECIFICATION ASTM B 8
	ASTM B 286
PVC:	TEMPERATURE RATING 105c
	VOLTAGE RATING 1000 VOLTS
	ELONGATION 300% AVERAGE
	TENSILE STRENGTH 3000 PSI AVERAGE
	SPECIFIC GRAVITY 1.34
	DUROMETER (SHORE) 47 (D)
	OXYGEN INDEX 25
	BRITTLE POINT -55c
	SPARK TESTED 7,100 VOLTS
	FINISHED O.D. .092"
	WEIGHT PER THOUSAND FEET 9.87#
REVISION:	MIL-DTL-16878H – PRINT REQUIRED

* OUR STANDARD IS PRINTED, IF NO PRINTING IS PREFERRED
PLEASE CALL THAT OUT AT TIME OF ORDER.

info@atlaswirecorp.com

Revision 11-15-16