

Mary Bufo

From: Raymond Khodeir <raymond_khodeir@ncsintl.com>
Sent: Tuesday, February 22, 2011 9:41 AM
To: Mary Bufo

*Hello Mary,
As requested.*

*305m # 35A1625 = 16-25C STR SRP/PVC 600V 105C= \$7250.00km
2-3 days
Best regards!*

Raymond Khodeir
Spécialiste en Fils et Câbles
Wire and Cable Specialist

National
Cable Specialists

☎ TEL: (514) 366-0666 Ext.105
(800) 361-1482
☎ FAX: (514) 366-7272
☎ E-mail: raymond_khodeir@ncsintl.com

www.nationalcablespecialists.ca

Avis : Ce message et toute pièce jointe sont la propriété de NCS International Cie et sont destinés seulement aux personnes ou à l'entité à qui le message est adressé. Si vous avez reçu ce message par erreur, veuillez le détruire et en aviser l'expéditeur par courriel. Si vous n'êtes pas le destinataire du message, vous n'êtes pas autorisé à utiliser, à copier ou à divulguer le contenu du message ou ses pièces jointes en tout ou en partie.

Notice: This message and any attachments are the property of NCS International Co. and are intended solely for the named recipients or entity to whom this message is addressed. If you have received this message in error please inform the sender via e-mail and destroy the message. If you are not the intended recipient you are not allowed to use, copy or disclose the contents or attachments in whole or in part.

National

Cable Specialists

Multi-Conductor (Unshielded) CSA/FT4/UL

Conductor : Stranded tinned copper


Insulation : Colour coded semi-rigid PVC

Jacket : Grey PVC

Temperature : -20C to +105C

Approvals : CSA certified CMG or CM to harmonized standard C22.2 No. 214 and UL 444. Certified to CSA standard C22.2 No. 210.2 - Type AWM. UL listed CL2 per standard UL13

Applications : PA systems, unbalanced intercom systems interconnecting cables, remote control circuits, low-voltage, broadcast & studio use, temperature control systems.



* Click on color code for description of colors

Product Code	Cond. Size	# of Cond.	Cond. Strand	Nom. Insul. Thickness (Inches)	Nom. Jacket Thickness (Inches)	Sugg. Working Voltage	Nom. O.D. (Inches)	Color Code	Ship. Weight Lbs/Mft
35A2202	22	2	7 X 30	.008	.015	600	.130	BLK/RED	9.1
35A2203	22	3	7 X 30	.008	.015	600	.138	BLK/RED/GRN	12.2
35A2204	22	4	7 X 30	.008	.015	600	.150	1	15.4
35A2205	22	5	7 X 30	.008	.023	600	.180	1	21.3
35A2206	22	6	7 X 30	.008	.023	600	.194	1	24.9
35A2207	22	7	7 X 30	.008	.023	600	.194	1	27.7
35A2208	22	8	7 X 30	.008	.023	600	.209	1	31.3
35A2209	22	9	7 X 30	.008	.023	600	.223	1	34.8
35A2210	22	10	7 X 30	.008	.023	600	.238	1	38.3
35A2212	22	12	7 X 30	.008	.023	600	.249	1	44.6
35A2215	22	15	7 X 30	.008	.023	600	.267	2	54.1
35A2220	22	20	7 X 30	.008	.023	600	.297	2	69.8
35A2225	22	25	7 X 30	.008	.030	600	.350	2	90.6
35A2230	22	30	7 X 30	.008	.030	600	.370	2	106.1
35A2240	22	40	7 X 30	.008	.030	600	.411	2	137.3
35A2250	22	50	7 X 30	.008	.030	600	.452	2	168.5
35A2002	20	2	7 x 28	.009	.015	600	.150	1	12.8
35A2003	20	3	7 x 28	.009	.015	600	.159	1	17.5
35A2004	20	4	7 x 28	.009	.023	600	.190	1	25.1
35A2005	20	5	7 x 28	.009	.023	600	.206	1	30.3
35A2007	20	7	7 x 28	.009	.023	600	.224	1	39.9
35A2009	20	9	7 x 28	.009	.023	600	.259	1	50.4
35A2012	20	12	7 x 28	.009	.023	600	.281	1	60.3
35A2015	20	15	7 x 28	.009	.030	600	.327	2	83.7

35A2019	20	19	7 x 28	.009	.030	600	.352	2	103.0
35A2025	20	25	7 x 28	.009	.030	600	.410	2	133.0
35A1802	18	2	16 X 30	.012	.023	600	.197	1	20.9
35A1803	18	3	16 X 30	.012	.023	600	.209	1	28.0
35A1804	18	4	16 X 30	.012	.023	600	.227	1	35.3
35A1805	18	5	16 X 30	.012	.023	600	.248	1	42.9
35A1806	18	6	16 X 30	.012	.023	600	.270	1	50.4
35A1807	18	7	16 X 30	.012	.023	600	.270	1	56.9
35A1808	18	8	16 X 30	.012	.023	600	.292	1	64.6
35A1809	18	9	16 X 30	.012	.030	600	.328	1	76.4
35A1812	18	12	16 X 30	.012	.030	600	.368	2	98.5
35A1815	18	15	16 X 30	.012	.030	600	.397	2	119.9
35A1819	18	19	16 X 30	.012	.030	600	.429	2	148.1
35A1825	18	25	16 X 30	.012	.032	600	.506	2	193.8
35A1830	18	30	16 X 30	.012	.032	600	.536	2	228.5
35A1840	18	40	16 X 30	.012	.050	600	.635	2	319.3
35A1602	16	2	26 X 30	.015	.023	600	.235	1	30.6
35A1603	16	3	26.30	.015	.023	600	.250	1	41.8
35A1604	16	4	26 x 30	.015	.023	600	.273	1	53.4
35A1605	16	5	26 x 30	.015	.023	600	.300	2	65.2
35A1607	16	7	26 x 30	.015	.030	600	.341	2	92.0
35A1609	16	9	26 x 30	.015	.030	600	.397	2	116.5
35A1612	16	12	26 x 30	.015	.030	600	.448	2	151.2
35A1615	16	15	26 x 30	.015	.032	600	.488	2	186.8
35A1619	16	19	26 x 30	.015	.032	600	.524	2	250
35A1625	16	25	26 x 30	.015	.050	600	.658	2	323.0
35A1402	14	2	41 X 30	.020	.023	600	.283	1	45.0
35A1403	14	3	41 x 30	.020	.030	600	.316	1	66.5
35A1404	14	4	41 x 30	.020	.030	600	.345	1	84.8
35A1405	14	5	41 x 30	.020	.030	600	.379	1	103.4
35A1407	14	7	41 x 30	.020	.030	600	.0413	2	138.7
35A1408	14	8	41 x 30	.020	.030	600	.449	2	157.5
35A1409	14	9	41 x 30	.020	.032	600	.488	2	178.1
35A1412	14	12	41 x 30	.020	.032	600	.552	2	232.1
35A1415	14	15	41 x 30	.020	.050	600	.633	2	305.9
35A1202	12	2	65 X 30	.030	.030	600	.378	1	75.8
35A1203	12	3	65 X 30	.030	.030	600	.403	1	104.9
35A1204	12	4	65 X 30	.030	.030	600	.442	1	134.9
35A1205	12	5	65 X 30	.030	.032	600	.491	2	167.3
35A1207	12	7	65 X 30	.030	.032	600	.538	2	225.5
35A1002	10	2	105 X 30	.030	.030	600	.457	1	113.2

GO TO:

[Multi-Conductor](#)
[Unshielded](#)
[Composite](#)
[Direct Burial](#)
[Overall Foil Shield](#)
[Miniature Overall Foil Shield](#)
[Overall Braid Shield](#)
[Overall Foil & Braid Shield](#)
[Lo-Cap Overall Foil & Braid Shield](#)

[Multi-Pair](#)
[Unshielded Intercom](#)
[Unshielded Intercom 105C](#)
[Unshielded](#)
[Overall Foil Shield](#)
[Low-Cap Overall Foil Shield](#)
[Overall Foil & Braid Shield](#)
[Low-Cap Overall Foil & Braid Shield](#)
[Individual Foil Shield](#)
[Miniature Individual Foil Shield](#)
[Low-Cap Individual Foil Shield](#)
[Individual & Overall Foil Shield](#)

[Station Wire](#)
[Inside](#)
[Direct Burial](#)

[Microphone & Guitar](#)
[Microphone Cable](#)
[Guitar Cable](#)

[Coaxial, Twinaxial & Video](#)
[50 ohm Transmission & Computer](#)
[Precision Video Cable](#)

75 ohm CATV, Video, Computer
93 ohm Computer
Twinaxial Computer

Back to Electronic Wire & Cable