

**1. CONDUCTOR:**

- 1.1 Size and Material: 10 37/.0167" AWG nickel-plated copper wire.
- 1.2 O.D.: .117" nom.

**2. INSULATION:**

- 2.1 Extruded PTFE.
- 2.2 Wall thickness: .020" nom.
- 2.3 Marking on the insulation: as per UL and CSA Standards.
- 2.4 O.D.: .157" nom.
- 2.5 Color: as per order (replace X in the part number and the description by 0-9 color code).

**3. PERFORMANCE:**

- 3.1 Voltage rating: 600 VAC R.M.S.
- 3.2 Temperature rating: 250°C


**4. REFERENCES:**

- 4.1 UL Subject 758 (AWM), Style 1659.
- 4.2 CSA Standard C22.2 No.210 (AWM), Class I Group A/B.

**CUSTOMER APPROVAL**

Sign: \_\_\_\_\_

Date: \_\_\_\_\_

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Daniel Curson</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com		
								Date: February 5, 2019				
								Verified: <i>David Holt</i>		Description: <b>XE20N1037/0167-X</b>		
								Date: February 5, 2019				
<b>UNCONTROLLED DOCUMENT</b> A later revision of this specification may exist.								Size: <b>A</b>	Scale: ---	Page: 1 of 1	Code Ident. No: <b>57104</b>	Specification No.: <b>F02343-X</b>